

BREATH SAFE

N95 Mask And N95 Mask With Respirator







Certifications































Product Composition

- Straps Thermoplastic Elastomer
- Nose Clip Aluminum
- Nose foam Polyurethane
- Filter Polypropylene
- Shell Polyester
- Cover web Polyester
- Respirator contains no components made from natural rubber latex
- Approximate weight of product: 0.35 OZ

Time usage and self life

- Replace the respirator when it becomes dirty, damaged, or difficult to breathe through
- 5 years from the date of manufacture
- Use By date on box in MM/YYYY format
- Store respirators in the original packaging, away from contaminated areas, dust, sunlight, extreme temperatures, excessive moisture, and damaging chemicals
- Store in temperatures between -4°F (-20°C)
 and +86°F (+30°C) and not exceeding 80% RH

Industry

- Pharmaceuticals: Material handling,
 Protection against COVID-19
- Agriculture: Pesticides, Grain dust, Pollen Dust, Insecticides handling
- Construction : Sanding, Drilling, Cutting, Carpentry
- Ceramics: Material handling, Molding, Raw material storage
- Mining: Drilling, Material handling
- Textiles: Spinning, Weaving
- Food & Beverages: Food processing and raw material handling

Use For

- Use for solid particulates and liquid mists in concentrations not exceeding 10X PEL/OEL
- Always follow User Instructions and use in manners as indicated

Do Not Use For

- DO NOT use for gases and vapors, oil aerosols, asbestos, arsenic, cadmium, lead, 4,4-methylene di-aniline (MDA), or abrasive blasting
- DO NOT use for particulate concentrations exceeding 10X PEL/OEL
- DO NOT use in any manner not indicated in the User Instructions

Certification & Standards

- ISO 45001:2018, ISO 9001:2015 Certified.
- CE certified.
- GMP Quality Product.
- RoHS Compliant



Specification

SR. NO.	TEST TYPE	SPECIFIED REQUIREMENT	RESULTS
1	Туре	6 Layer	6 Layer
2	Color	Grey	Grey
3	Check for Integrity	Proper Ultrasonically welded layer	Complies
4	Absorbance Test	NMT 0.1 (OD)	Complies
5	Residue on Evaporation	NMT 5 mg	Complies
6	Acidity or Alkalinity	NMT 1 ml of 0.001 M HCL/NaOH	Complies
7	Heavy Metals ion Test	NMT 1 ppm	Complies
8	Reducing (Oxidizable) Test	NMT 2 ml of 0.002 M KMnO4	Complies
9	Breathing Resistance	NMT 49.0 Pascal/cm2	Complies
10	Bacterial Filter Efficiency(BFE)	NLT 95%	Complies
11	Particle Filter Efficiency(PFE)	NLT 95%	Complies
12	Splash Resistance (mm Hg)	NLT 120	Complies
13	Toxicity	Non Toxic	Complies



Fitting instructions



 Clean your hands with soap and water or hand sanitizer



2. Hold the mask by the ear loops and place a loop around each ear.



3. Mold or pinch the stiff edge to the shape of your nose



4. Put the bottom of the mask over your mouth and chin



5. Avoid touching the front of the mask when wearing

Removal instructions



 Clean your hands with soap and water or hand sanitizer



2. Avoid touching the front of the mask. Only touch the ear loops.



3. Hold both of the ear loops and remove the mask



Contact Us

ESAPLLING PRIVATE LIMITED

Office # 513, Rainbow Plaza, Shivar Chowk, Pimple Saudagar Pune, Maharashtra – 411017

- **9**18002331116
- **(**+91) 7083652833
- support@esaplling.com